

Use CECOR's SE10 single phase electric Sumpcleaner/Filter anywhere in the plant.

- Available in 90, 140, 175, 300, 400, 500 and 600 gallon capacity.
- Pumping rate to 60 gallon per minute.
- Generates suction to 17" Hg (Mercury) or 231" water.
- 115/60/1 electricals
- Efficient 1 Horsepower electric motor.

The SE10 Sumpcleaner/Filter is also available as a Combination Sumpcleaner/Filter and Coolant Dispenser.

Caution: Machines must not be used for flammable fluids (fuels, paints, solvents, etc.) . Avoid use in extra-high temperature or spark-hazard environments (ovens, welding areas, etc.) .



SE10-90PT Sumpcleaner/Filter.



Standard F10 Filter

F10 - 1.0 Cubic Foot Filter

The F10 strainer basket and fabric liner has a capacity of 1.0 cubic foot and is standard on the SE10. The reusable filter has built in grips and is small enough for one person to lift. Course, fine and polypropylene filter bags are standard with the F10 filter basket.



Optional F23 Filter

F23 - 2.3 Cubic Foot Filter (Optional)

With a 2.3 cubic foot capacity, the F23 filter is fitted for fork lift or hook hoist handling. Patented compound linkage and rotary latch controls the bottom opening door for safe emptying. The filter assembly comes complete with a polypropylene filter sleeve. The F23 filter is optional on the SE10. Optional fine weave polypropylene filter sleeve available.



SE10-175PL6 Sumpcleaner/Filter.

Tank Size: 90, 140, 175, 300, 400, 500 and 600 gallon capacity.

Motor: 1 HP Electric Motor
Volts 115
Amps 13.4
Hertz 60
Phase 1

Pump: Rotary, vane-type vacuum pump

Pumping Rate: Up to 60 gallons per minute.

Suction Lift: 17" Hg (Mercury) or 231" water

Pressure Discharge: 6 PSI (pounds per square inch) with safety backup valve.

Filter: F10 Filter has 1 cubic foot capacity and is standard on the SE10. Optional F23 (2.3 cubic feet) capacity is recommended when coolant is loaded with chips and swarf.

Spill Prevention: Automatic overflow protection. All discharge ports are valved.

Hose: 1 1/2" I.D. x 16' oil-resistant PVC suction/discharge hose including quick-disconnect couplers and suction tools.

Cleaning Tools: Flared Nozzle
Flexible Nozzle
Straight Nozzle

Power Cord: 15 feet standard
50 feet available

See page 33 for information on base options

Options

| Model Number | Tank Size | Cleanout Door | Transport | Wheels | Dimensions | Shipping Weight | TW Base | PL6 Base | PLW Base | CB1 Base | CB2 Base | CB3 Base | CB4 Base | CB5 Base | F23 Filter | Floor Squeegee | | |
|--------------|------------|---|--|--|-----------------------------------|-----------------------------------|-----------|----------|----------|----------|----------|----------|----------|----------|------------|----------------|---|---|
| SE10-90PT | 90 gallon | 8" x 10" with a 1 1/2" drain port | PT Base for push or tow transport. | Two 12" x 3" poly wheels and one 8" x 3" poly caster | 68" long 30" wide 45" high | 850 lbs. | X | X | X | X | X | X | X | X | X | X | | |
| SE10-140PT | 140 gallon | | | | 68" long 34" wide 54" high | 690 lbs. | X | X | X | X | X | X | X | X | X | X | X | X |
| SE10-175PT | 175 gallon | | | | 80" long 34" wide 54" high | 805 lbs. | X | X | X | X | X | X | X | X | X | X | X | X |
| SE10-300TW | 300 gallon | 16" diameter with hinged door with a 2 1/2" drain port. | TWBase - Tow Bar with pinle-eye hitch to accommodate most in-plant tugs or tractors. | Mounts two heavy-duty 16" x 4" wheels and one 12" x 3" swivel casters. | 98" long 40" wide 62" high | 1085 lbs. | S | NA | X | X | X | X | X | X | X | X | | |
| SE10-400TW | 400 gallon | | | Mounts two heavy-duty 16" x 4" wheels and two 12" x 3" casters. | 99" long 48" wide 68" high | 1490 lbs. | S | NA | X | X | X | X | X | X | X | X | X | |
| SE10-500TW | 500 gallon | | | Mounts two heavy-duty 16" x 5" wheels and two 12" x 3" swivel casters. | 111" long 48" wide 70" high | 1503 lbs. | S | NA | X | X | X | X | X | X | X | X | X | X |
| SE10-600CB1 | 600 gallon | | | CB1 Base -Custom base for mounting on trailer or truck. | Not applicable | 121" long 42" wide 60" high | 1699 lbs. | NA | NA | NA | X | X | X | X | X | X | X | X |

NOTE: Engineering Specifications subject to change without notice.

X = Available
S = Standard
NA = Not Available