



ECOVAC 300 3KW - Oil Filtration and Sump Cleaner

Mobile sump cleaning and filtering unit with 85 gallon tank capacity which will simultaneously pick-up, filter and return cleaned oil in one continuous operation.



Ecovac 300 3 KW

Suction Power:	230 Volts, 60 HZ, single phase, 14 Amps, max input 4.0 Hp
Suction Performance (Air):	106 SCFM
Suction Lift (water):	12 foot (maximum)
Suction rate:	52 gpm (water) using the 2 inch suction hose

Pump Discharge Unit: 1/2 Hp induction motor driven open impeller centrifugal pump, protected by a large in-tank filter. The oil resistant discharge hose (10 feet x 1 inch) is fitted with a trigger actuated nozzle. Discharge rate is 20 gpm (water) @ 100 psi.

Controls: Splash proof On/Off Switch for suction and discharge, incorporating float actuated electrical shut-off.

Filter Basket: 10 Gallon capacity with 200 micron replacement nylon filter bag. (Other filter bags sizes are available)

Drain/Cleaning: 9 inch cleaning access port

Construction: Heavy duty mild steel tank mounted (2) 5 inch (swivel front) and (2) 10 inch (fixed rear) casters – for easy mobility.

Dimensions 54” x 27” x 48” (L x W x H)

Weight: 360 pounds (Empty)

Electrical Requirement: 230 volts, 60 Hz, 20 Amp circuit, Single Phase

Price \$10,100.00

(Price Subject to change without notice)