




Turbo-Centrifuge MZF-T07

Suitable for separating particles from all sorts of industrial fluids



Technical Information	
Flowrate	1 to 20 LPM Oil 1 to 30 LPM Emulsion
Medium	Oil and Emulsion
PH	6.5 until 9.5 / 6.5 until 10.0
Temperature	60° C
Quality of cleanliness	Down to 1 micron
Material Housing	Steel / Stainless Steel
Material Rotor	Aluminium / Aluminium anodized
Rotor capacity	5.2 dm ³
Sludge Volume	2 to 3 kg
Type of cleaning	2 phase
Rotor Speed	50 Hz = 2850 RPM 60 Hz = 3400 RPM
Separating Factor	900 g to 1180 g (1 g = gravity acceleration)
Noise emission	< 70 dBa
Drive	Directdrive
Drive Power	0.8 kW
Solids discharge	Manuell
Liquid return	Under pressure
Controlpanel	Including
Inlet	> 585 mm
Dimension	> 640 x 450 x 585 mm
Weight	> 75 kg
Options	Clean Liquid Tank Pumps Chiller

!!!New with drum drain!!!

(which means waste disposal of dry sludge)



Turbo-Separator
a Turbo-International company

Turbo-Separator AG
Bleikenstrasse 48
9630 Wattwil
Switzerland
+41 71 987 70 20
+41 71 987 20 29
www.turbo-separator.ch
info@turbo-separator.ch